

OMNI Pro

MAXIMISING YOUR COLLABORATION POTENTIAL

VCD

PIXEL TECHNOLOGY OPTIONS:
SMD
COB FLIP CHIP COMMON CATHODE

ULTRA-WIDE - 21:9 - ALL-IN-ONE

Ultra-Wide Aspect Ratio

A 21:9 display enhances productivity, offers immersive gaming and movie experiences, and is ideal for creative work, reducing the need for multiple monitors.

- Enhanced productivity with more screen space.
- Immersive gaming experience with wider field of view.
- Optimal for watching movies without letterboxing.
- Ideal for creative tasks like video editing and design.
- Replaces the need for dual-monitor setups.
- Beneficial for programmers with multiple windows.



BENEFITS OF COB FLIP CHIP COMMON CATHODE:



Improved Thermal Management:

Reduces heat, prolonging LED lifespan and enhancing performance.



Increased Energy Efficiency:

Lowers power consumption, saving energy and reducing costs.



Enhanced Durability:

Direct mounting on substrate increases shock and vibration resistance.



Better Color Accuracy:

Ensures superior color accuracy and contrast, ideal for high-quality displays.

VCD



Ultra Wide Ratio



Improved Energy Efficiency




2 Pixel Choices: SMD or COB



HDR Capable





Dual Backup/ Redundancy



The OMNI Pro is an unparalleled choice, expertly crafted to excel in challenging settings such as control rooms, command centers, luxurious home cinemas, and sophisticated corporate applications. It blends cutting-edge technology with robust design, ensuring optimal performance and reliability in these demanding environments

Dual Backup/ Redundancy

The OMNI Pro features full, power and data redundancy. This significantly improves stability and reliability in mission critical environments.





Control Rooms



Corporate



E-Sports



Home Cinema

SPECIFICATIONS

SMD				
Pixel Pitch (mm)	1.25	1.56	1.8	2.5
Cabinet Resolution (W×H)	640×270	512×216	424×180	320×135
Module Size (mm) (W×H)	200×337.5			
Cabinet Size (mm) (W×H×D)	800×337.5×38			
Brightness (nits)	≤800			≤1200
Gray Scale (bit)	14~16			
Pixel Calibration	Support brightness and color calibration			
Colour Temperature	2000 ~ 12000 (adjustable)			
Control System	Synchronous control			
Drive Mode	Constant current drive (compatible)			
Frame Rate (Hz)	50/60			
Refresh Rate (Hz)	≥3840			
Working Voltage (V)	AC100 ~ 240V (50~60Hz)			
Max. Power Consumption (W/m ²)	≤725	≤680	≤600	≤780
Avg. Power Consumption (W/m ²)	≤280	≤270	≤240	≤310
Lifetime (H)	≤100,000			
Operating Temp (°C / °F)	-10 ~ +40 / +14 ~ +104			
Storage Temp (°C / °F)	-20 ~ +60 / -4 ~ +140			
Operating Humidity	10% ~ 80%			
Cabinet Weight (kg/lbs)	6.8 / 15			

COB	
Pixel Pitch (mm)	1.25 1.56
Cabinet Resolution (W×H)	640×270 512×216
Module Size (mm) (W×H)	200×337.5
Cabinet Size (mm) (W×H×D)	800×337.5×38
Brightness (nits)	Standard brightness≤1500 High brightness≤3500
Gray Scale (bit)	14~16
Pixel Calibration	Support brightness and color calibration
Colour Temperature	2000 ~ 12000 (adjustable)
Control System	Synchronous control
Drive Mode	Constant current drive (compatible)
Frame Rate (Hz)	50/60
Refresh Rate (Hz)	≥3840
Working Voltage (V)	AC100 ~ 240V (50~60Hz)
Max. Power Consumption (W/m ²)	≤450
Avg. Power Consumption (W/m ²)	≤180
Lifetime (H)	≤100,000
Operating Temp (°C / °F)	-10 ~ +40 / +14 ~ +104
Storage Temp (°C / °F)	-20 ~ +60 / -4 ~ +140
Operating Humidity	10% ~ 80%
Cabinet Weight (kg/lbs)	6.8 / 15

*All data contained is subject to change.



Please contact us if you have any questions,
we're always happy to help

www.vodvisual.com

China Head Office

5D-701 Software
Industry Base, Haitian
2nd Road, Nanshan
District, Shenzhen,
Guangdong
cn@vodvisual.com
Tel: +86 755 2267 7271

UK Office

Unit 3 Clearwater Business
Park Frankland Road
Swindon, SN5 8YZ
United Kingdom

Tel: +44 (0) 20 3852 9500

UK Showroom

The Pavilion
Merchant Square
London, W2 1JZ
United Kingdom

Tel: +44 (0) 20 3832 9500

USA Office

22 Boston Wharf Road,
7th Floor,
Boston, MA 02210
United States

Tel: +1 (833) 533-7836

USA Showroom

123 Heiman Street,
Suite 200, San Antonio,
Texas 78205
United States

Tel: +1 (833) 533-7836